

## **TECHNICAL INFORMATION**

### **BEST-Primer C**

**BEST-Primer C** is a solvent containing primer for the pretreatment of polyolefines and non-polar synthetic materials, e.g. PP, PE, PTFE or of silicones before bonding with BEST-CA instant adhesives. BEST-Primer C consists of 99% CFC/FC free carrier agent and the actual pretreatment agent.

**BEST-Primer C** is a primer to be used in combination with all BEST-CA adhesives. It is suitable for the pretreatment of bonding surfaces made of non-polar synthetic materials which are difficult to bond, e. g. polyethylene, polypropylene, polyoximethylene, silicones, polyamide > 6.6, PTFE. Subsequent bonding with BEST-CA 212 delivers best results.

### **INSTRUCTIONS FOR USE**

Apply BEST-Primer C on the bonding surface (brush, spray or dip). Allow product to dry off completely (5 – 10 minutes) before application of adhesive and assembly. Bonding process has to be completed within 24 hours after application of BEST-Primer C.

### **CURING**

With all BEST-CA instant adhesives fixture time is reached within 10 – 30 seconds.

### **STORAGE**

Store in a cool, well ventilated place. Keep container tightly closed. Shelf life in unopened original container: 12 months (room temperature)

### **HEALTH AND SAFETY STANDARDS**

Hazard Statements: Highly flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. For further information please see corresponding material safety data sheets.

#### **General**

The data and information above correspond to the current know-how of BEST-Klebstoffe GmbH & Co.KG. Our information and data have been developed from laboratory tests and extensive practical experience. It is the user's responsibility to perform receiving inspections and to determine suitability for the user's purpose of any production methods. We disclaim all warranties expressed or implied, that any product will have specific properties for a particular purpose. BEST-Klebstoffe GmbH & Co. KG reserves the right to change the contents of this document as necessary.

Revision: 150622

Revision Date: 22.06.2015