

## **TECHNICAL INFORMATION**

### **BEST-Chainspray with MoS<sub>2</sub>**

**BEST-chain spray** with MoS<sub>2</sub> is suitable for permanent inside and outside lubrication of bearings, gear- and worm drives, roller- and ball bearings, o-rings, wire cables and all types of joints, couplings and chains.

#### **PROPERTIES**

- highly effective - excellent creep properties
- very good adhesive properties
- excellent corrosion protection
- water repellent
- temperature range: - 40°C up to + 150°C

#### **DIRECTIONS FOR USE**

Clean parts to be treated of oily and greasy residue. Shake product well before use. Spray on from a distance of approx. 20 cm, allow to dry for approx. 5 - 10 minutes.

#### **HEALTH AND SAFETY STANDARDS**

Hazard Statements: Extremely flammable aerosol. Harmful to aquatic life with long lasting effects. For further information please see corresponding material safety data sheets.

#### **General**

The data and information above correspond to the current know-how of BEST-Klebstoffe GmbH & Co.KG. Our information and data have been developed from laboratory tests and extensive practical experience. It is the user's responsibility to perform receiving inspections and to determine suitability for the user's purpose of any production methods. We disclaim all warranties expressed or implied, that any product will have specific properties for a particular purpose. BEST-Klebstoffe GmbH & Co. KG reserves the right to change the contents of this document as necessary.

Revision: 150622  
Revisionsdate: 22.06.2015

TI\_E\_Chainspray\_Rev\_150622

Page 1 of 1